

Multi-Roll 44

Multi-Roll 44 is a lightweight, non-combustible mineral wool roll, designed to provide thermal and acoustic insulation in lofts. The roll can be used in any other application where a lightweight insulation is required and may be split to allow the user the choice of any of the three commonly required widths. Manufactured from recycled glass bottles, Multi-Roll 44 is strong, flexible and resilient.

IDEAL APPLICATION



LOFTS



The benefits of Multi-Roll 44:

- Value for money - cost effective
- Thermal performance - K Value of 0.044W/mK
- Acoustic performance - excellent sound absorption
- Environmental - 84% recycled glass bottles, zero ODP & GWP, BRE Green Guide Rating A+ and HCFC & CFC Free
- Fire performance - Fire classification A1 non-combustible
- Easy-to-fit - simple installation process

Product dimensions and information

THICKNESS mm	LENGTH m	WIDTH mm	AREA m ²	R-VALUE m ² K/W	CODE
100	9.17	1200, 2x600, 3x400	11.00	2.25	5810
150	6.03	1160, 2x580, 3x386	7.00	3.40	5815
170	5.30	1160, 2x580, 3x386	6.15	3.85	5817
200	4.50	1160, 2x580, 3x386	5.22	4.50	5830

24 rolls per pallet

U-Values

U-Value (W/m ² K)	0.16	0.14	0.12
Thickness of insulation between joists (mm)	100	100	150
Thickness of insulation over joists (mm)	170	200	200

Typical U-Values achieved when using Multi-Roll 44 in a standard loft application

